1 B DL 2019-04-09 INITIAL RELEASE BILL OF MATERIALS DESCRIPTION
Cable - 4Cx16, Black, SOOW MANUFACTURER PART NO. 1575 mm 1 EA Connector - C3 Series, Female, 4 Position Connector - Combicon Series, Female, 4 Position
Connector - Combicon Series, Female, 4 Position
Heat Shrink Tubing - Black, 2-1 ratio, 3/4"
Heat Shrink Tubing - Black, 2-1 ratio, 3/16"
Ferrule - 16AWG, Black Phoenix Contat Qualtek 5 N/A Qualtek TE Connectivity/AMI SPECIFIED TOOLING REQUIREMENTS MANUFACTURER
TE Connectivity/AMP TOOLING REQUIREMENTS ARE MANDITORY AND MUST BE CLEARED BY CLEARPATH ROBOTICS ENGINEERING BEFORE CHANGING 1575mm +/- 5mm 1425mm +/- 5mm P1 To base panel P2 To electrical panel 0000 CONNECTOR TOP VIEW CONNECTOR FACE VIEW

> A ALL HEATSHRINK TUBING WILL COVER TRANSITIONS BETWEEN OUTER JACKETING TO INNER SLEEVING AND/OR DISCRETE WIRES B HEATSHRINK TUBING SHALL BE USED WHEN TERMINATING ALL CONTACTS IN 4POS CONNECTOR (2)

C TERMINALS ARE SOLDERED/CLEANED TO CLASS 3 (IPC SPECIFICATIONS) BEFORE BEING COVERED WITH HEAT SHRINK TUBING

D LABEL TO BE MARKED ONLY WITH 6-DIGIT ITEM NUMBER

CONNECTION TABLE										
ITEM	PIN NO.	CONTACT ITEM	WIRE ITEM	WIRE COLOUR	WIRE SIGNAL	ITEM	PIN NO.	CONTACT ITEM		
	1	N/A	1	Pink	+12V		1			
2	2			Black	GND	2	2	6		
-	3			Green	RX	3	3			
	4			White	TX		4			

1

2

			DESIGNED	Jason Be	erringer		2019-04-09	ITEM DESCRIPTION				
CLEARPATH			DRAWN	Dana l	ına Leslie		2019-04-09					
	PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF		CHECKED		*		*	RS232 - BASE TO ELEC. PANEL CABLE ASSY.			ASSY.	
			APPROVED		:	7 -	*					
			APPROVED		:		*					
			LAST M	2019-04-09		9-04-09		ITEM 1	NUMBER	REV.		
	CLEARPATH ROBOTICS INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CLEARPATH ROBOTICS INC. IS PROHIBITED.		SIZE B	DO NOT SC.	ALE	N	IOT TO SCALE	SHEET 1 OF 1	014672		В	